

ME 80-100-112-132-160

IC06/IC17/IC37

Motori C.C. eccitazione separata - Potenza da 0.44KW a 31KW

Shunt field D.C. motors - Power from 0.44KW to 31KW

CARATTERISTICHE PRINCIPALI




- Motori C.C. a norme CEI ed IEC.
- Eccitazione separata con serie stabilizzatrice.
- Poli ausiliari su tutte le grandezze.
- Tensione armatura 170V-290V-400V-440V.
- Protezione IP23 (IP54 per IC37)- servizio continuo S1.
- Servoventilati IC06 da ventilatore addossato.
- Servoventilati IC17/IC37 da ventilatore esterno.

MAIN FEATURES

- D.C. motors according to CEI and IEC standards.
- Shunt field with series stabilizer.
- Interpoles on all sizes.
- Armature voltage 170V-290V-400V-440V.
- IP23 protection (IP54 for IC37)- continuous duty S1.
- Force ventilated IC06 by blower on the motor.
- Force ventilated IC17/IC37 by outside blower.



Tipo / Type	ØAC	L	Potenza a / Power at			Potenza a / Power at		
			1500rpm	2000rpm	3000rpm	1500rpm	2000rpm	3000rpm
ME 80 R	157	285	0.44 KW	0.6 KW	0.88 KW	-	-	-
ME 80 S	157	305	0.6 KW	0.74 KW	1.1 KW	-	-	-
ME 100 R	192	310	0.74 KW	1 KW	1.5 KW	-	-	-
ME 100 S	192	330	1 KW	1.3 KW	2 KW	-	-	-
ME 100 T	192	330	1.25 KW	1.6 KW	2.4 KW	-	-	-
ME 112 R	220	335	1.6 KW	2.2 KW	3.2 KW	1.8 KW	2.5 KW	3.7 KW
ME 112 S	220	335	2.1 KW	2.7 KW	4 KW	2.35 KW	3.1 KW	4.6 KW
ME 112 T	220	375	2.4 KW	3.2 KW	4.9 KW	2.8 KW	3.7 KW	5.6 KW
ME 112 L	220	405	2.8 KW	3.7 KW	5.6 KW	3.1 KW	4.2 KW	6.25 KW
ME 132 R	260	390	3.3 KW	4.7 KW	6.7 KW	4.4 KW	5.5 KW	8.1 KW
ME 132 S	260	415	-	-	-	5.2 KW	6.7 KW	10.3 KW
ME 132 T	260	440	-	-	-	6.6 KW	8.8 KW	13.2 KW
ME 132 L	260	480	-	-	-	9.6 KW	12.5 KW	18.4 KW
ME 160 R	320	525	-	-	-	13.2 KW	17.6 KW	25.7 KW
ME 160 S	320	585	-	-	-	15.4 KW	20.6 KW	31 KW



IEC B5	IEC B14
71	-
80	-
90	-
100	100
112	112
132	132
160	160

Tipo / Type	ØD	H
ME 80	14-16-19	80
ME 100	19-24	100
ME 112	24-28	112
ME 132	28-38	132
ME 160	38-42-48	160

OPZIONI :

- Flange e alberi speciali
- Dinamo e/o encoder
- Freno di sicurezza
- Fili uscenti
- Avvolgimenti per tensioni da batteria

OPTIONS :

- Special shafts and flanges
- Tacho and/or encoder
- Safety brake
- Free wires
- Windings for battery voltage.